

### GENERATOR SPECIFICATION

|                           |                             |
|---------------------------|-----------------------------|
| <b>Voltage</b>            | 230/115                     |
|                           | Neutral bonded to earth/CTE |
| <b>Phase</b>              | 1                           |
| <b>Frequency</b>          | 50Hz                        |
| <b>Prime Power (PRP)</b>  | 6.0 kVA / 4.8 kW            |
| <b>Alternator</b>         | NSM M100SG                  |
| <b>Fuel tank capacity</b> | 24.0 Litres                 |
| <b>Autonomy 75% load</b>  | 17.0 Hours                  |
| <b>LWA</b>                | 84                          |
| <b>dBA @ 7M</b>           | 59                          |

### ENGINE SPECIFICATION

|                            |                    |
|----------------------------|--------------------|
| <b>Engine</b>              | Yanmar L100NES     |
| <b>Emissions certified</b> | N/A                |
| <b>Cylinders</b>           | Single             |
| <b>Distribution</b>        | O.H.V.             |
| <b>Aspiration</b>          | Normally aspirated |
| <b>Cooling</b>             | Air                |
| <b>Displacement</b>        | 0.435 Litres       |
| <b>Rpm</b>                 | 3000               |

**YANMAR**



3 Year Engine  
Warranty (Limited)



### DIMENSIONS

| Application | Length mm | Width mm | Height mm | Weight KG |
|-------------|-----------|----------|-----------|-----------|
| Trolley Dry | 1270      | 785      | 970       | 210       |
| Trolley Wet | 1270      | 785      | 970       | 231       |
| Skid Dry    | 980       | 640      | 970       | 197       |
| Skid Wet    | 980       | 640      | 970       | 218       |

## CONTROL PANEL

- Key start complete with low oil pressure, high engine temperature, low fuel level & battery charge shutdown/warning lamps.
- MCB overload protection.
- 230V : 1 x 32A & 1 x 16A BS4343 sockets.
- 115V : 1 x 32A & 2 x 16A BS4343 sockets.
- Overload protection for each individual socket.
- Hours run meter.

## STANDARD FEATURES

- Ultra low noise acoustic canopy - **only 59dba @ 7m.**
- Gas strut canopy roof.
- Industrial two wheeled trolley kit.
- Lifting eye.
- Self bleeding.
- 12V fuel lift pump.
- Low oil pressure, high engine temperature & low fuel level shutdowns.

## DSE 3110 AUTO START CONTROL MODULE OPTION



- The module will display warnings, shutdowns & engine status information on the back-lit LCD screen.
- Engine shutdowns include, high engine temperature, low oil pressure and low fuel level.
- Monitoring & protecting AC Volts & Frequency (Hz).
- Hours run counter.
- Battery voltage monitoring.
- Remote start function.
- Licence free PC software.



- Deep Sea 4510 control module upgrade available. Full generator monitoring and telemetry compatible.

## POWER DEFINITION

### Prime Power (PRP) :

Applicable for supplying power to varying electrical load for unlimited hours in accordance ISO 8528-1.

## OPTIONS

- Skid version available.
- Customised socket arrangement on request.
- AVR (Automatic Voltage Regulator).
- ATS Panel (Automatic Transfer Switch).
- RCD earth leakage protection.
- Chalwyn valve/Spark arrestor.
- Mains battery charger.
- Auto start/stop programmable 7-day timer (DSE 3110 required).
- Telemetry monitoring service available (DSE 4510 control module upgrade required).